

Metberg TC6036 Tracked Conveyor



The TC6036 tracked conveyor from Metberg Enviro offers a high quality build at an outstanding price. Built with high strength steel and with a heavy duty under carriage, the TC6036 is simple to set up and operate.

The TC6036 is also available in a wheeled variant and comes in 40ft to 80ft lengths, with hydraulic or electric options.

Engine / Controls

- CAT 2.2 power unit
- Corded remote control

Frame

- Deep folded plate frame with heavy duty cross bracing for strength & stability
- Hydraulic folding head section

Idlers

- 35 degree CEMA B standard idlers
- Impact bed at feedpoint

Undercarriage

- 2.4m (8 ft) tracks with 400mm (16 inch) shoes
- Hydraulic raise and lower
- Galvanized trestle with variable feed and discharge heights

Belt

- 3-ply vulcanized
- Flat belt 900mm (3ft / 36 in) wide
- Self adjusting polyurethane belt cleaner

Feedboot

- Drilled for liners
- 140mm (5.5 in) long with adjustable rubber skirting

Dimensions

- 18m tracked long stacked conveyor
- 900mm (36 in) wide, 60 ft long conveyor belt
- Transportation length: 11.3m (37 ft)
- Transportation Height: 2.5m (8 ft 4 in)
- Width: 2.3m (7 ft 5 in)
- Weight: 8,500Kg

Other

- Can be transported in a 40 ft container
- Mesh under conveyor guarding to 5.5 ft from ground
- Side skirting 140mm (5.5 ft) from ground
- All nip points guarded
- Remote greasing to all bearing from ground level
- Max stockpiling height 8m (26 ft) (at 26 degrees)
- Max stockpiling capacity 570 m³ (745 cu. yd)